

Clack Corporation



WATER SPECIALIST 1" CONTROL VALVE



shown with optional bypass

- **Solid state microprocessor with easy access front panel settings**
- **Three modes of operation; meter immediate, meter delayed, or time clock delayed**
- **Double backwash feature offers optimum regeneration, cleaning ability, and efficiency**
- **36 selectable pre-programmed regeneration cycles**
- **Days override feature; 1 – 28 days available**
- **Backwash and brining ability to 22" diameter tanks**
- **Downflow/upflow regeneration**
- **Stores system configuration and operation data in nonvolatile memory**
- **Coin Cell Lithium battery back-up with an 8 hour carry over**
- **12-volt output AC Adapter provides safe and easy installation**
- **Control valve design provides optimum service and backwash rates**
- **Treated water regenerant refill**
- **Reliable and proven DC drive**

Water Specialist 1" Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.25" NPS
Cycles	up to 6
Valve Material	Noryl (1) or equivalent
Regeneration	downflow/upflow

FLOW RATES

Service @15 psi drop (includes bypass and meter)	27 gpm
Backwash @ 25 psi drop (includes bypass)	27 gpm
Cv Service	7.0
Cv Backwash	5.4

OPERATING PRESSURES

Minimum/Maximum	20 psi – 125 psi
-----------------------	------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° – 110° F
-----------------------	--------------

METER

Accuracy	± 5%
Flow Rate Range.....	0.25 – 27 gpm
Gallon Range.....	20 – 50,000 gallons
Totalizer	1000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot.....	1.050" OD Pipe (¾" NPS)
Drain Line	¾" or 1" NPT
Brine Line	¾" or ½" OD Poly Tube
Mounting Base.....	2 ½" - 8 NPSM
Height From Top Of Tank.....	7 ¾"
Weight	4.5 lbs.

ELECTRICAL SPECIFICATIONS

AC Adapter

	<u>U.S.</u>	<u>International</u>
Supply Voltage	120V AC.....	230V AC
Supply Frequency	60 Hz.....	50 Hz
Output Voltage	12V AC.....	12V AC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener	6" – 22" diameter
Water Filter (2).....	6" – 22" diameter

CYCLES OF OPERATION (Softener Downflow)

Cycle	Range of times minutes
1. Backwash 1 st (upflow).....	6 - 12
2. Regenerate Draw/Slow Rinse (downflow)	45 - 75
3. Backwash 2 nd (upflow)	3 - 12
4. Fast Rinse (downflow)	3 - 8
5. Regenerant Refill (in service with treated water).....	As Programmed
6. Service (downflow)	

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of General Electric

2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area